

## M3W EN-Series (Meet EU Standards)



Ethernet for stable connection



4G optional for any location



WIFI for convenient home use



Rs485 interface enable Dynamic Load Balancing and Solar Charging



Ocpp communication with CMS



Smart app with full function



Tethered and integrated socket meet different demands



Wall-mount or floor stand installation



Special one-piece metal backcover



Anti-scraping tempered glass front cover



4.3-inch highlight display



Type A 30ma + 6ma DC leakage protection  
CE, ROHS, REACH, LVD, RED approved



Item	M3W132EN	M3W316EN	M3W332EN
Maximum Power	7kW/32A -230VAC	11kW/16A -400VAC	22kW/32A -400VAC
Basic info	Tethered/Socket	Optional	
	Connector	Type 2	
	Dimension(H*W*D)mm	410*260*164	
	Material	Tempered glass front+metal plate back	
	Colour	BLACK front + white back or OEM Color	
	Indicator	4 indicators	
	Display	4.3-inch	
Features	Ethernet(RJ45)	Yes	
	RFID	Yes	
	WIFI	2.4GHz	
	4G	Optional	
	RS485	Optional	
	OCPP1.6J	Optional	
	App	Optional	
	Dynamic Load Balancing	Optional	
	Solar Charging	Optional	
Safety	Ingress Protection	IP54, IK08	
	Residual current protection	Type A 30mA+6mA DC	
	Over load protection	Yes	
	Over/Under voltage protection	Yes	
	Short circuit protection	Yes	
	Earh Leakage Protection	Yes	
	Ground Protection	Yes	
	Surge protection	Yes	
	Over temperature	Yes	
	Certification	CE, RoHS, Reach, LVD, RED	
	Certification Standard	EN IEC 61851-1	
Environment	Installation	Wall/Pole mounted	
	Storge Temperature	-40~75°C	
	Work Temperature	-30~55°C	
	Work Humidity	3%~95%	
	Work Altitude	<2000m	